



262 Flush bolt - 6" square end

- An exceptionally smooth working flush bolt with sharp, crisp lines
- Double action spring design provides automatic holding of brass bolt in projected or retracted position, and assures ease of operation in conjunction with deep cup finger hole
- Made from polished cast brass
- Bolt tip is 1/2" diameter
- Bolt throw is 1"
- Bolt backset is 15/32"

Certifications

- Meets ANSI A156.16, L04201

Mounting

- 5 X 5/8" FPHSMS
- 8 X 3/4" FPHSMS

Dimensions

| Body size (Width X Length X Depth) | Strike size (Width X Length) |
|---------------------------------------|---------------------------------|
| 3/4" x 6" x 1-11/32" | 7/8" x 1-3/4" |

Finishes

| BHMA | Description | Substrate | US |
|------|-------------------|-----------|-------|
| 605 | Bright brass | Brass | US3 |
| 609 | Satin brass | Brass | US5 |
| 613 | Oil rubbed bronze | Brass | US10B |
| 619 | Satin nickel | Brass | US15 |
| 625 | Bright chrome | Brass | US26 |
| 626 | Satin chrome | Brass | US26D |

Custom finishes are available as engineering special, consult customer service.

Hinges & pivots

A

Pulls & plates

B

Flush bolts & coordinators

C11

Latches, catches & bolts

D

Stops

E

Exterior hardware

F

Miscellaneous hardware

G