

## Latches, catches and bolts

### Invisible latches

# CL11

## Invisible latch

- Invisible latch is ideal for installations where no visible latch or strike is desired
- Unit can be installed at the top, bottom or side of the door
- Can be mortised into the stop or surface mounted to the stop
- Recommended for use on small panels, cabinet doors or lightweight doors
- Not recommended for use on hollow lightweight doors with single point access to area
- Operation is simple, latching is accomplished by a slight push
- To unlatch the door, a harder push releases the door and pushes the door out
- Brass and plastic construction
- Applies 13 pounds to open the door
- Units packed with wood screws



### Specifications

Material substrate	Made from brass and plastic
Certifications	Meets ANSI/BHMA A156.9, B03272

### Dimensions

Body	Strike
1 1/4" W x 1 7/8" H x 7/16" T	9/16" W x 1 5/16" H x 9/16" Projection


### Available accessories

- Security pin screws

# CL12

## Invisible latch

- Invisible latch is ideal for installations where no visible latch is desired
- Unit can be installed at the top, bottom or side of the door
- Can be mortised into the stop or surface mounted to the stop
- Recommended for use on larger panels, cabinet doors or lightweight doors
- Not recommended for use on hollow lightweight doors with single point access to area
- Operation is simple, latching is accomplished by a slight push
- To unlatch the door, a harder push releases the door and pushes the door out
- Brass and plastic construction
- Applies 27 pounds to open the door
- Units packed with wood screws



### Specifications

Material substrate	Made from brass and plastic
Certifications	Meets ANSI/BHMA A156.9, B03272

### Dimensions

Body	Strike
1 1/4" W x 2 1/4" H x 9/16" T	5/8" W x 1 13/16" H x 9/16" Projection

### Available accessories

- Security pin screws

# CL14

## Invisible latch, auxiliary pusher

- Aid in the operation of the CL11 and CL12 where hinges or surrounding conditions prevent smooth operation of doors
- Provides 1 1/16" throw
- Nylon pusher
- Applies 10 pounds to open the door
- Units packed with wood screws



### Specifications

Material substrate	Made from brass
Certifications	Meets ANSI/BHMA A156.9, B13282

### Dimensions

Body
2 15/16" L x 1 11/16" W x 5/8" D

### Available accessories

- Security pin screws

### CL11, CL12 and CL14 Finishes

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	US3
606	Satin Brass	Brass	US4
612	Satin Bronze	Brass	US10
626	Satin Chrome	Brass	US26D

For other colors, consult factory.