LG1/LG7

Lock guard (with and without security pin)

- LGI incorporates security frame pin to prevent separation of the door and frame LG7 does not incorporate the security frame pin
- Ideal for use with mortise or cylindrical locks
- Unit covers the latch bolt area of the door and lock, thereby providing added protection from burglars, vandals or normal abuse
- Non-handed
- Easy installation
- Through bolted with carriage bolts and nuts

Specifications

opeenieutiene		2	
Material substrate	Made from 13 gauge stainless steel, 12	WxH	Bolt ce
	gauge steel (LG1 only) or brass (LG1 only)	3" x 11 1/2"	10 ¹ / ₂ "
Certifications	UL10C Listed (3 hour)		

Dimensions Bolt center to center

Certifications		
Finishes		

BHMA	Description	Substrate	Finish	
600*	Primed for paint	Steel	USP	
603*	Zinc plated	Steel	US2G	
695*	Dark bronze painted	Steel	SP313	
606*	Satin brass	Brass	US4	
612*	Satin bronze	Brass	US10	
630	Satin stainless	Stainless steel	US32D	

*Not available on LG7. For other colors, consult factory.

I G10

Lock guard

- Ideally suited for use with rose or escutcheon 2³/₄" wide or less
- For use with type 86 mortise and type 161 cylindrical locks (ANSI/BHMA 156.13 Series 1000 and ANSI/BHMA 156.2 Series 4000)
- Unique design provides maximum security, virtually eliminating the
- opening between door and frame at the latch point
- Non-handed
- 2 welded mounting studs. No exposed fasteners on face of unit

Specifications		Dimensions	
Material substrate	Made from 13 gauge stainless	WxH	Stud center to center
	steel, 12 gauge steel	2 ¹ / ₂ " x 9 ¹ / ₂ "	8 ¹ /2"
Certifications	UL10C Listed (3 hour)		
E ireiche e			

Finishes

BHMA	Description	Substrate	Finish
600	Primed for Paint	Steel	USP
630	Satin Stainless	Stainless steel	US32D

For other colors, consult factory.

Available accessories

Security pin fasteners

