

VON DUPRIN® 3327A/3527A Surface Mounted Vertical Rod Device

27 Top Latch



3327A and 3527A for all types of single and double doors, UL listed for Panic Exit Hardware. Devices are ANSI A156.3 – 2001 Grade 1. The 3527A has a smooth mechanism case and the 3327A has grooved case. The surface vertical rod device is non-handed except when the SS (Signal Switch) option is used. See opposite page for available outside trim and device functions.

3327A/3527A fits door stiles as narrow as 1 3/4" (44mm). Newly designed device has a one piece center case cover.

The 3327A/3527A devices are available in the following finishes; US3, US4, US10, US26, US26D, US28, 313AN and 315AN. See the inside cover for finish chips.

Specifications

Device Lengths	3' 2'4" to 3' (711mm to 914 mm) Door Size 4' 2'10" to 4' (864 mm to 1219 mm) Door Size
Strikes	Top – 266 – Dull Black, Bottom – 248L4 & 304L – Unfinished Optional Strikes – see page 20
Dogging Feature	Hex key dogging standard
Dogging Options	CD Cylinder Dogging see page 26 LD Less Dogging see page 26
Electric Options	LX Latchbolt Monitor Switch see page 22 RX Pushpad Monitor Switch see page 22 RX2 Double Pushpad Monitor Switch see page 22 SS Signal Switch see page 23 EL Electric Latch Retraction see page 23 ALK Alarm Exit Kit see page 22
Miscellaneous Options	PN Pneumatic Latch Retraction see page 26 LBR Less Bottom Rod see page 27 GBK Glass Bead Kit see page 27 PL Pullman Latch see page 27
Fasteners & Sex Bolts (SNB)	Includes 1 3/4" (44mm) – 2 1/4" (57mm) Wood & Metal Doors #425 SNB furnished standard for end case #325 SNB furnished standard for EO (exit only device) #325 SNB furnished for top and bottom latches
Latch Bolt	Deadlocking Anti-friction Top & Bottom Bolt 5/8" (16mm) throw
Device Centerline from Finished Floor	39 5/8" (1006mm)
Door Undercut	1/4" (7mm)
Center Case Dimensions	8 3/16" x 2 13/32" x 1 9/16" (208mm x 62mm x 40mm)
Mechanism Case Dimensions	2 1/4" x 2 1/4" (57mm x 57mm)
Top and Bottom Latch	4 1/2" x 2 1/8" x 1 1/2" (114mm x 54mm x 38mm)
Vertical Rods	1/2" square tubing, standard rods accommodate 7'(2134mm) door Top rod length is 34 15/16" (887mm) Bottom rod length is 31 1/4"(794mm) Extension rods available 1' (205mm) or 3'(914mm) for doors over 7' One piece top rod available for 8'(2438mm)-10'(3048mm) door
Projection	Pushbar Neutral – 3 13/16" (97 mm) Pushbar Depressed – 3 1/16" (78 mm)

27 Bottom Latch



266
Top Strike



248L-4
Bottom Strike
for use with
Threshold












304L
Bottom Strike

See page 31 for How to Order specification

© 2005 Ingersoll-Rand. May be copied for use with specification submittal.

VON DUPRIN® 3327A/3527A Surface Mounted Vertical Rod Device Trim

	Exit only	Dummy Trim Pull when dogged	Night Latch Key retracts latchbolt	Night Latch Key retracts latchbolt Optional Pull Required	Thumbturn Key locks & unlocks
					
Product Description	3327A-E0 3527A-E0	3327A-DT 3527A-DT	3327A-NL 3527A-NL	3327A-NL-OP 3527A-NL-OP	3327A-TL 3527A-TL
Trim Description	—	386DT	386NL	388	374T x 386
Base Size	—	7 ¹⁵ / ₃₂ " h X 1 ⁵ / ₈ " w (190x41mm)	7 ¹⁵ / ₃₂ " h X 1 ⁵ / ₈ " w (190x41mm)	7 ¹ / ₂ " h X 1 ¹¹ / ₁₆ " w (190x43mm)	7 ¹ / ₂ " h X 1 ¹¹ / ₁₆ " w X 7 ⁷ / ₈ " d (190x43x22mm)
Grip Size	—	8 ¹ / ₂ " h X 4 ⁵ / ₁₆ " w (216x110mm)	8 ¹ / ₂ " h X 4 ⁵ / ₁₆ " w (216x110mm)	—	—
Projection	—	2 ⁷ / ₁₆ " (62mm)	2 ⁷ / ₁₆ " (62mm)	1" (25mm)	1 ¹³ / ₁₆ " (46mm)
ANSI Function	01	02	03	03	11-12 Field Selectable
Cylinder Type	—	—	Rim	Rim	1 ¹ / ₄ " Mortise
Optional Trim (See page 19)	—	x 360L-DT x550 DT x IVES 8190	—	x550 DT x IVES 8190 10"	x 392-6

	Thumbturn-Blank Escutcheon Always Operable (No Cylinder)	Lever Key Locks & Unlocks	Lever-Blank Escutcheon Always Operable (No Cylinder)	Thumbturn Key Locks & Unlocks	Thumbturn Always Operable (No Cylinder)
					
Product Description	3327A-TL-BE 3527A-TL-BE	3327A-L 3527A-L	3327A-L-BE 3527A-L-BE	3327A-T 3527A-T	3327A-T-BE 3527A-T-BE
Trim Description	374T-BE x 386	360L	360L-BE	360T	360T-BE
Base Size	7 ¹ / ₂ " h X 1 ¹¹ / ₁₆ " w X 7 ⁷ / ₈ " d (190x43x22mm)	7 ¹ / ₂ " h X 1 ¹¹ / ₁₆ " w X 7 ⁷ / ₈ " d (190x43x22mm)	7 ¹ / ₂ " h X 1 ¹¹ / ₁₆ " w X 7 ⁷ / ₈ " d (190x43x22mm)	7 ¹ / ₂ " h X 1 ¹¹ / ₁₆ " w X 7 ⁷ / ₈ " d (190x43x22mm)	7 ¹ / ₂ " h X 1 ¹¹ / ₁₆ " w X 7 ⁷ / ₈ " d (190x43x22mm)
Grip Size	8 ¹ / ₂ " h X 4 ⁵ / ₁₆ " w (216x110mm)	—	—	—	—
Projection	1 ¹³ / ₁₆ " (46mm)	3" (76mm)	3" (76mm)	1 ¹³ / ₁₆ " (46mm)	1 ¹³ / ₁₆ " (46mm)
ANSI Function	—	08 or 09 Field Selectable	—	11 or 12 Field Selectable	—
Cylinder Type	—	1 ¹ / ₄ " Mortise	—	1 ¹ / ₄ " Mortise	—
Optional Trim (See page 19)	x 392-6	—	E360L-BE See Page 18	—	E360T-BE See Page 18

**Note: 360L & 360T used on Wood Door require the 33A-WDA cover plate
374T used on Wood Door require #10-WDA cover plate.**

For optional trims and functions see page 19