

Overhead Holders & Stops



Innovation, Quality,
Customer Service...

1000SL Series Concealed Mount, Heavy Duty, Slim Line



Standard Features

- Concealed mount
- Heavy duty
- Slim line channel designed for aluminum store front doors
- Stop and hold-open functions available
- Single or double acting doors
- Non-handed
- For interior or exterior use on frequent traffic and heavy weight doors
- Standard installation from 85° to 110° of opening (5° increments)
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- 1-3/4" minimum door thickness
- UL Listed as Miscellaneous Fire Door Accessories for use on wood fire doors rated up to 90 minutes and metal fire doors rated up to 3 hours (stop function only)
- Average weight per unit = 5 lbs.

Options Available

(see page B-5 for details)

- **SEC** - Security fasteners
- **LL** - For lead-lined door applications
- **LS** - Less shock-absorbing spring for special applications
- **N** - All stainless steel (non-ferrous) components for wet environments to prevent corrosion (stop function only)
- **T** - Jamb bracket is replaced with a threaded pivot screw and nylon washer
- **SPECIAL** - Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom template and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

Door Frame Opening		Model Number	
Hinges or Offset Pivots	Center Hung	Hold Open	Stop
27" - 29-15/16"	30" - 32-15/16"	1011SL	1021SL
30" - 35-15/16"	33" - 38-15/16"	1012SL	1022SL
36" - 39-15/16"	39" - 42-15/16"	1013SL	1023SL
40" - 43-15/16"	43" - 46-15/16"	1014SL	1024SL
44" - 52"	47" - 54"	1015SL	1025SL
ANSI Code		C01511	C01541

Material

- **Stainless steel** is the standard base material for arm and jamb bracket for all finishes.

Specify When Ordering

- Model Number
- Finish
- Option(s), if applicable



Architectural Builders Hardware Manufacturing, Inc.
1222 Ardmore Avenue, Itasca, IL 60143
Tel: 630-875-9900 • Fax: 630-875-9918 / 800-932-9224
Web: www.abhmfg.com • Email: abhinfo@abhmfg.com