

Latches, catches and bolts

Ball catches

349

Ball catch, dual adjustable - rounded corners

- Recommended for lower frequency opening applications
- For catch in door installations
- Radiused corners allow easy installation with a router
- Dual adjustment for door clearance and holding strength
- Lip strike is designed for use where strike is mounted in jamb
- Free rolling ball insures smooth, positive and trouble-free action
- Adjustable threaded barrel compensates for various door clearances
- Adjustable spring tension
- Rounded corners on strike lip for safety
- Units packed with wood screws



Specifications

Material substrate	Made from wrought brass
Certifications	Meets ANSI/BHMA A156.9, B23013

Dimensions

Face plate	Bore	Strike
1" W x 2 1/8" H	7/8" DIA x 1 3/8" D	1 3/8" W x 2 1/8" H, lip to center - 7/8"

Finishes

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	US3
606	Satin Brass	Brass	US3
609	Blackened Brass	Brass	US5
612	Satin Bronze	Brass	US10
613	Oil Rubbed Bronze	Brass	US10B
619	Satin Nickel	Brass	US15
625	Bright Chrome	Brass	US26
626	Satin Chrome	Brass	US26D
643e/716	Aged Bronze	Brass	643e/716
622	Matte Black	Brass	BLK

For other colors, consult factory.

2

Elbow catch

- Ideal for use on the inactive leaf of a pair of cabinet doors
- Surface applied, making installation simple
- Spring loaded function - surface applied, making installation simple
- Made from cast aluminum

Specifications

Material substrate	Made from wrought brass
Certifications	Meets ANSI/BHMA A156.9, B33023

Dimensions

Plate	Strike
1 3/8" H x 5/8" W	1 3/16" H x 5/8" W

Finish - aluminum

Ives number	A3	A5	A14	A15	A92	A716
BHMA	666		669	670	673	

