

FS13 Dome stop

- Standard FS13 for use where no threshold is used
- Heavy-duty cast dome stops constructed of brass
- Unique riser design of R14 (below) allows easy conversion to threshold application
- Units are packed with fasteners sufficient for mounting in all types of floor construction, including concrete
- Replaceable- grey rubber bumper

Certifications

Meets ANSI/BHMA A156.16, L12141

Material substrate

Made from cast brass

Available accessory items

Security pin screwsGrey rubber bumper

Dimensions

- Overall height: 1"
- Base height: 5/32"
- Base diameter: 1–3/4"

R14 Dome stop rise

See finishes below

Adapts the FS13 Dome stop to threshold use.

Material substrate

Made from cast brass

See finishes below

Dimensions

- Riser height: 5/16"
- Base diameter: 1-3/4" round
- One piece dome stop for use with thresholds
- Heavy-duty cast dome stops constructed of brass

Description

Bright brass

Satin brass

Satin bronze

Oil rubbed bronze

Bright chrome

- Units are packed with fasteners sufficient for mounting in all types of floor construction, including concrete
- Grey rubber bumper

Certifications

Meets ANSI/BHMA A156.16, L12161

Material substrate

Made from cast brass

Available accessory items

Security pin screwsGrey rubber bumper

FS13, R14 and FS17 Finishes

Grey rubber burnp

See finishes below

BHMA

605

606

612

613

625

Dimensions

Substrate

Brass Brass

Brass

Brass

Brass

Brass

- Overall height: 1-11/32"
- Base height: 1/2"
- Base diameter: 1-3/4" round

Finish

US3

US4

US10

US10B

US26

US26D

D ag

Hinges & pivots

Pulls & plates

Flush bolts &

Latches, catches & bolts

E2

626 Satin chrome

FS17 Dome stop