

A
Hinges & pivots



MB1V

B
Pulls & plates



MB2V

C22
Flush bolts & coordinators



MB3V

D
Latches, catches & bolts

E
Stops

F
Exterior hardware

G
Miscellaneous hardware

MB1F, MB2F and MB3F Fire rated mounting brackets MB1V, MB2V and MB3V

- Allows for fire-rated stop mounted hardware to be properly installed without damaging the COR Coordinators, such as fire-rated surface vertical rod exit device strikes.
- Latch will need to be lowered to compensate for the height of the coordinator and mounting bracket.
- MB-V are designed for Von Duprin 8827-F soffit latch.

Certifications

- Meets ANSI A156.3 Type 21A

Material substrate

- Cold rolled steel

Sizes

Product	Jamb depth	Stop width	Dimensions
MB1F	5"	1-1/2" - 2-1/4"	4" W x 3" D x 1-5/8" T
MB1V	5"	1-1/2" - 2-1/4"	4" W x 3" D x 1-5/8" T
MB2F	5-7/8"	2-3/8" - 3-1/4"	4" W x 3" D x 1-5/8" T
MB2V	5-7/8"	2-3/8" - 3-1/4"	4" W x 3" D x 1-5/8" T
MB3F	6-7/8"	Over 3-3/8"	4"W x 3-1/2" D x 1"T
MB3V	6-7/8"	Over 3-3/8"	4"W x 3-1/2" D x 1"T

Finishes

BHMA	Description	Substrate	US
600	Primed for paint	Steel	USP
-	Flat black painted	Steel	BLK
689	Aluminum painted	Steel	SP28

Custom finishes are available as engineering special, consult customer service