

**Latches, catches and bolts**

**Roller latches**

# RL1152

**Roller latch**

- Recommended for higher traffic applications
- Combination of RL30 roller latch and angle stop
- Actuation is simple, closing of the door causes the roller to fall in the depression of the strike, thereby holding the door closed
- The projection of the roller is easily adjustable using adjusting screws on the face of the unit
- Maximum projection of the roller is  $\frac{3}{8}$ " allowing for variance in the door clearance
- Nylon roller standard
- Forged brass construction
- Units packed with wood screws



**Specifications**

Material substrate	Made from forged brass
Certifications	Meets ANSI/BHMA A156.16, E19111

**Dimensions**

<b>Body</b>	<b>Strike</b>
1 $\frac{3}{8}$ " W x 2" H x $\frac{7}{8}$ " D	1" W x 2 $\frac{1}{8}$ " H x $\frac{3}{8}$ " D

**Finishes**

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	US3
606	Satin Brass	Brass	US4
612	Satin Bronze	Brass	US10
613	Oil Rubbed Bronze	Brass	US10B
619	Satin Nickel	Brass	US15
622	Matte Black	Brass	BLK
625	Bright Chrome	Brass	US26
626	Satin Chrome	Brass	US26D
643e/716	Aged Bronze	Brass	643e/716

For other colors, consult factory.

**Available accessories**

- Security mounting screws
- Brass roller
- Silencers

# STK685/STK685L

**Optional strikes**

**STK685 strike**


- Dimple of strike centered on strike

**STK685L strike**


- Location of strike dimple is variable
- Please specify location of dimple from edge of frame to centerline of the dimple - B  
Dimple will be located B +  $\frac{3}{16}$ " to accommodate lip

**Both strikes:**

- Custom make strike for doors that swing both directions
- For use with roller latches
- Specify frame depth - A. Overall strike length will be A +  $\frac{3}{8}$ " to accommodate  $\frac{3}{16}$ " lip on each side
- Units packed with wood and machine screws to meet most field conditions



STK685



STK685L

**Specifications**

Material substrate	Made from $\frac{3}{32}$ " brass
--------------------	----------------------------------

**Dimensions**

<b>Strike width</b>	<b>Strike length</b>
2 $\frac{1}{4}$ "	Specified frame width + $\frac{3}{8}$ "

**Finishes**

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	US3
606	Satin Brass	Brass	US4
612	Satin Bronze	Brass	US10
613	Oil Rubbed Bronze	Brass	US10B
625	Bright Chrome	Brass	US26
626	Satin Chrome	Brass	US26D

For other colors, consult factory.

Introduction  
Table of contents  
Hinges and pivots  
Pulls, push bars and plates  
Flush bolts, strikes and coordinators  
Latches, catches and bolts  
Door stops, holders and silencers  
Exterior hardware  
Miscellaneous hardware