


9130 SERIES


TOP JAMB SINGLE DOOR (OFFSET/BUTT HINGE, CENTER PIVOT, PULL, STANDARD COVER) MOUNTING



TOP JAMB SINGLE DOOR (OFFSET/BUTT HINGE, CENTER PIVOT, PULL, FULL COVER) MOUNTING

MAXIMUM OPENING

Template allows 90 degree power opening and 90 degree manual opening.



- **Butt Hinges** should not exceed 5" (127 mm) in width.
- **Reveal** should not exceed 1/8" (3 mm).
- **Head Frame** minimum 2" (51 mm).
- **Top Rail** minimum 2" (51 mm).
- **Opening and Closing Time** are variable by adjustments to the electronic control module located on the operator assembly. Maximum hold open time adjustable up to approximately 30 seconds.
- **System Diagram** see "AUTOMATIC OPERATORS" section pages 53 for typical system wiring and page 56 for electrical data.

Contact LCN Product Support for installation assistance.

9130 SERIES

MOTOR GEARBOX

MOTOR GEARBOX ASSEMBLY, 9130-3454S

Driving mechanism for operator. (Switch included).
For 27" unit.

MOTOR GEARBOX ASSEMBLY (W/O SWITCH), 9130-3454

Driving mechanism for operator. (Switch not included).
For full length unit (36").

BRACKETS

MOUNTING BRACKET, 9130-3018

Standard mounting bracket.

SWITCH BRACKET – 29" CABLE, 9130-3351-1

Bracket used to locate switch at end of cover on full length unit.

SWITCH BRACKET – 41" CABLE, 9130-3351-2

Bracket used to locate switch at end of cover on full length unit.

CONTROL BOXES

CONTROL BOX, (120v), 9130-3462

Electronic controlling device with power supply output and power boost feature for Benchmark.

COVERS

METAL COVER, 9130-72MC

Standard, 27", non-handed, extruded aluminum cover.

FULL METAL COVER, 9130-72FC

36", non-handed, extruded aluminum cover.

COVER INSERT 9130-163

Used to cover operator shaft opening. (Includes 2 pieces).


COVER END CAP INSERT, 9130-163-1

Used to cover switch hole opening.


COVER END CAP, 9130-334

Black plastic end caps. (Includes 9130-163-1 cover and cap insert).


3454
3454S




3018




3351-1
3351-2




3462




72MC
72FC



163



334



Note (*334 includes 163-1)

9130 SERIES

TRACKS

STANDARD TRACK, 9130-3038

Standard, non-handed track.

TRACK END CAP, 9130-73

Black plastic end caps.

ROLLER, 9130-3034

Quiet low friction roller assembly.




ARMS

STANDARD ARM, 9130-3077T

Non-handed arm. Track roller not included.

STANDARD ARM with 9130-3077PLCM

Non-handed arm and standard non handed track.



9130 SERIES

TABLE OF SIZES

DOOR WIDTH



NOTE: For All Benchmark Series.

30" minimum door width for 27" pull operator.

36" door width only for full length pull operator.

HOW-TO-ORDER 9130 SERIES OPERATORS

1. SPECIFY FINISH

- Standard Anodized Finish _____
Aluminum or Dark Bronze.

Operator will be shipped with:

- STANDARD MOTOR GEARBOX,
 - STANDARD CONTROL BOX,
 - MOUNTING BRACKET,
 - 27" METAL COVER,
 - STANDARD ARM (3077T),
 - STANDARD TRACK w/TRACK ROLLER,
 - WOOD and MACHINE SCREW PACK
- Unless options listed below are selected.*

OPERATOR OPTIONS

COVER

- 36" Full Cover.

ORDERING INFORMATION