Markar HG305 Adjustable Hinge Guard

Standard Features

Barrel Type Hinge
.187" diameter Stainless Steel pin (rod)
Medical bearings
Stainless Steel end pins
Material
Heavy-duty 14 gauge Stainless Steel
Finishes
US32D Satin Stainless Steel (630)
Standards
ANSI/BHMA Standard A156.26 Grade 1
Mounting Hardware
Fasteners concealed when door
is closed
Custom 12-24 x 11/16" S.S Phillips Flat
Head Undercut TEK Screws

Capacity
Supports weights up to 600 lbs.
4'0" maximum door width
Standard Sizes
6'8", 7'0", 7'2", 8'0", 10'0"
Hole Pattern
Symmetrically templated
Handing
Not required for standard 7'0", 8'0" or
10'0". Handing required for 6'8" and
7'2" and for most optional features
listed

Fire Rating
3 hours- hollow metal doors
90 minutes- hollow metal and
composite
20 minutes- wood doors



Classified in accordance with UL10C for positive pressure




Fire-rated label

Windstorm Products is constructed in accordance with Guidelines FEMA 320 & FEMA 361.

Optional Features


Finish
US32 Bright Stainless Steel (629)
Scratch-Resistant Powder Coated Paint
Fasteners
Adjust-A-Screw™ for correcting frame
fit problems up to ³/8"




Other Features
Custom lengths- specify in inches
Custom hole pattern
Dutch door hinges- suffix "DDP"
Hospital tips – suffix "HT"
Raised barrel – suffix "RB"
Welded end pins
Security studs

Electrical Modifications
Adjustable Monitoring Switch - suffix "AMS"
Current Transfer Prep - suffix "CTP"
Electrical Transfer Access Prep - suffix "ETAP"
ElectroLynx®
EL4 (4 wire), EL8 (8 wire), EL12 (12 wire)
PoE (9 wire)

The integral hinge guard protects the door from dings and gouges from carts and gurneys while providing clean lines and aesthetic appearance. Our HG products also have fire ratings up to and including 3 hours. Not only that, but the wrap-around edge guard protects the door from unsightly dents and gouges and will deflect objects, preventing further damage.



Door Closed



Door Open 180°

