



Application

- Interior or exterior doors
- Doors may be single or double acting
- Non-handed
- Recommended for moderate traffic, medium weight doors

Features

- Low profile
- Low profile concealed channel designed for installation in aluminum storefront doors
- Heavy shock absorber spring provides 5-7° compression before dead stop
- Complete screw kit allows for installation in wood or metal door and frame
- For security areas, Torx® screws optional
- Standard architectural finishes
- Durable slider cam
- 110° maximum opening
- 1-3/4" minimum door thickness
- Channel is 1-1/4" wide by 1/2" deep
- Hanging means other than standard butts or offset pivots require special templating and pricing. Consult factory
- Available in stop function only

Compliance

- ANSI/BHMA A156.8, Grade 1 Certified
- UL listed for fire door assemblies

DOOR OPENING CHART (IN INCHES)

| Butts Offset Pivots | Center Hung Pivots | Model Number |
|---------------------|--------------------|--------------|
| Door Opening | | Stop |
| *24 - 28 | — | 6-136 |
| 28-1/16 - 33 | 30 - 36 | 6-236 |
| 33-1/16 - 38 | 36-1/16 - 41 | 6-336 |
| 38-1/16 - 43 | 41-1/16 - 46 | 6-436 |
| 43-1/16 - 48 | 46-1/16 - 50 | 6-536 |

*Butt hung only on this size door. No swing clear hinges.



Experience a safer
and more open world