

The global leader in
door opening solutions

Rockwood 2960 - Automatic Flush Bolt with Bottom Fire Bolt



Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630

FACE PLATE SIZE:

1 1/8" x 2 1/4"

WEIGHT:

0.9 lbs.

Specifications:

MATERIAL:

Brass

FASTENERS:

4 ea. #8 x 1" Flat Head Sheet Metal Screws, 4 ea. #8 x 3/4" Flat Head Combo Screws, 2 ea. Plastic Anchors

FEATURES:

- Patent #7,410,195
- Durable, tested over 1 million cycles
- Smaller profile adds stability to the door
- Only two 1 1/8" diameter holes for easier door preparation
- Preparation prevents the veneer from splitting at the corners of the door
- Quiet & smooth activation
- Fully automatic; opening active door retracts top bolt
- Non-handed
- Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
- Low (3 lbs. maximum) closing force. ADA Compliant
- Adjustable Bolt Head Rod: bolts can be vertically adjusted 1/2" for unusual clearances
- For up to 4'w x 9'h fire rated wood core & composite doors up to 20 minutes fire rating
- UL Listed



300 Main Street
Rockwood, Pennsylvania 15557
P: 800.458.2424 • F: 800.922.9212
www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.