


580-12

580-8

## Surface Bolts No. 580, 582 Series

- Material:** No. 580: Steel, stainless steel  
No. 582: Stainless steel
- Finishes:** US3, US10, US10B painted, US26D, US32D
- Fastener:** No. 580: 8 ea. #10 x 1<sup>1</sup>/<sub>4</sub>" FH SMS, 8 ea. #10 - 24 x 1" FH MS  
No. 582: Bolt: 4 ea. #10 - 24 x 1<sup>1</sup>/<sub>2</sub>" PH MS; 4 ea. #10 x 1<sup>1</sup>/<sub>4</sub>" PH WS  
Strikes: 6 ea. #10 - 32 x 1<sup>1</sup>/<sub>2</sub>" FH MS; 6 ea. #10 - 32 x 1<sup>1</sup>/<sub>2</sub>" FH WS
- Other:** 1<sup>1</sup>/<sub>8</sub>" bolt throw, 1<sup>1</sup>/<sub>4</sub>" x 3<sup>3</sup>/<sub>4</sub>" bolt material
- Features:**
- No. 580 Series bolts are UL listed for use on inactive leaf of a pair of 3-hour labeled fire doors
  - No. 580 and No. 582 series both include a universal top strike and a mortise bottom strike
  - No. 582 Series has a bracket for padlock (padlock not included)
- Options:** Sex bolts available for extra secure mounting



582-8

| No.    | Bolt Length | Weight   | ANSI A156.16 |
|--------|-------------|----------|--------------|
| 580-8  | 8"          | 1.1 lbs. | L04161       |
| 580-12 | 12"         | 1.4 lbs. | L04161       |
| 580-18 | 18"         | 1.7 lbs. | L04161       |
| 580-24 | 24"         | 2.0 lbs. | L04161       |
| 582-8  | 8"          | 1.3 lbs. |              |
| 582-12 | 12"         | 1.6 lbs. |              |

## Heavy Duty Surface Bolts No. 585 Series

- Material:** Steel
- Finishes:** US26D
- Fastener:** Bolt: 4 ea. 1<sup>1</sup>/<sub>4</sub> - 20 x 2<sup>1</sup>/<sub>4</sub>" FH MS  
4 ea. 1<sup>1</sup>/<sub>4</sub> - 20 x 1<sup>5</sup>/<sub>8</sub>" sex bolts  
Strike: 2 ea. #14 x 2<sup>1</sup>/<sub>2</sub>" FH SMS, 2 ea. Plastic Anchors  
2 ea. 1<sup>1</sup>/<sub>4</sub> - 20 x 1" FH MS, 2 ea. 1<sup>1</sup>/<sub>4</sub> - 20 Lead Anchors
- Other:** 1<sup>1</sup>/<sub>4</sub>" bolt throw, 3<sup>3</sup>/<sub>4</sub>" x 3<sup>3</sup>/<sub>4</sub>" bolt material
- Features:**
- UL listed for use on inactive leaf of a pair of 3-hour labeled fire doors
  - Includes a universal top strike and a mortise bottom strike
  - Locks in both the up and down position
  - Bolt locks automatically when thrown – can be released only by pressing knob toward door while retracting
  - Can be used on any type of door
  - Accommodates padlock



| No.    | Bolt Length | Weight   | ANSI A156.16 |
|--------|-------------|----------|--------------|
| 585-12 | 12"         | 3.9 lbs. | L04161       |
| 585-24 | 24"         | 6.1 lbs. | L04161       |

800-458-2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved.  
Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.

**ASSA ABLOY**

The global leader in  
door opening solutions