

Experience a safer  
and more open world

## Rockwood BF166 - 45° Offset Door Pulls



### Specifications:

**MATERIAL:**

Aluminum, Brass, Bronze, or Stainless Steel

**FASTENER:**

1/4"-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**OPTIONS:**

- Back to back mounting in pairs — use BTB suffix and mounting type number (BF166BTB16)
- Concealed mounting single pulls — use C suffix and mounting type number (BF166C17)
- Advise if door thickness is other than 1 3/4"
- Heavy duty versions of most fastening types available — use suffix HD to fastening type number (BF166BTB16HD)
- Use Y prefix (YBF166) when ordering pulls with base plates, Y plate diameter is 1 1/4"; recommended for use on wood and glass doors

### Available Finishes:

- US28/628
- 313/710
- 315/711
- Powder Coat
- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630
- US32/629
- US32DMS
- US32D316
- US32316

**MATERIAL SIZE:**  
1" dia.

**CTC:**  
8"

**OVERALL:**  
9"

**BASE:**  
1"

**PROJECTION:**  
3 1/2"

**CLEARANCE:**  
2 1/2"

**OFFSET:**  
2 3/4"

**WEIGHT:**  
2.8 lbs.

ANSI A156.6: J402

Experience a safer  
and more open world

## Rockwood BF167A - 45° Offset Door Pulls



### Specifications:

#### MATERIAL:

Aluminum, Brass, Bronze, or Stainless Steel

#### FASTENER:

1/4"-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

#### OPTIONS:

- Back to back mounting in pairs — use BTB suffix and mounting type number (BF167ABTB16)
- Concealed mounting single pulls — use C suffix and mounting type number (BF167AC17)
- Advise if door thickness is other than 1 3/4"
- Heavy duty versions of most fastening types available — use suffix HD to fastening type number (BF167ABTB16HD)
- Use Y prefix (YBF167A) when ordering pulls with base plates, Y plate diameter is 1 1/4"; recommended for use on wood and glass doors

### Available Finishes:

- US28/628
- 313/710
- 315/711
- Powder Coat
- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630
- US32/629
- US32DMS
- US32D316
- US32316

MATERIAL SIZE:  
1" dia.

CTC:  
9"

OVERALL:  
10"

BASE:  
1"

PROJECTION:  
3 1/2"

CLEARANCE:  
2 1/2"

OFFSET:  
2 3/4"

WEIGHT:  
3.0 lbs.

ANSI A156.6: J402

Experience a safer  
and more open world

## Rockwood BF167 - 45° Offset Door Pulls



### Specifications:

#### MATERIAL:

Aluminum, Brass, Bronze, or Stainless Steel

#### FASTENER:

1/4"-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

#### OPTIONS:

- Back to back mounting in pairs — use BTB suffix and mounting type number (BF167BTB16)
- Concealed mounting single pulls — use C suffix and mounting type number (BF167C17)
- Advise if door thickness is other than 1 3/4"
- Heavy duty versions of most fastening types available — use suffix HD to fastening type number (BF167BTB16HD)
- Use Y prefix (YBF167) when ordering pulls with base plates, Y plate diameter is 1 1/4"; recommended for use on wood and glass doors

### Available Finishes:

- US28/628
- 313/710
- 315/711
- Powder Coat
- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630
- US32/629
- US32DMS
- US32D316
- US32316

MATERIAL SIZE:  
1" dia.

CTC:  
10"

OVERALL:  
11"

BASE:  
1"

PROJECTION:  
3 1/2"

CLEARANCE:  
2 1/2"

OFFSET:  
2 3/4"

WEIGHT:  
3.2 lbs.

ANSI A156.6: J402

Experience a safer  
and more open world

## Rockwood BF168 - 45° Offset Door Pulls



### Specifications:

#### MATERIAL:

Aluminum, Brass, Bronze, or Stainless Steel

#### FASTENER:

1/4"-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

#### OPTIONS:

- Back to back mounting in pairs — use BTB suffix and mounting type number (BF168BTB16)
- Concealed mounting single pulls — use C suffix and mounting type number (BF168C17)
- Advise if door thickness is other than 1 3/4"
- Heavy duty versions of most fastening types available — use suffix HD to fastening type number (BF168BTB16HD)
- Use Y prefix (YBF168) when ordering pulls with base plates, Y plate diameter is 1 1/4"; recommended for use on wood and glass doors

### Available Finishes:

- US28/628
- 313/710
- 315/711
- Powder Coat
- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630
- US32/629
- US32DMS
- US32D316
- US32316

MATERIAL SIZE:  
1" dia.

CTC:  
12"

OVERALL:  
13"

BASE:  
1"

PROJECTION:  
3 1/2"

CLEARANCE:  
2 1/2"

OFFSET:  
2 3/4"

WEIGHT:  
3.6 lbs.

ANSI A156.6: J402

Experience a safer  
and more open world

## Rockwood BF169 - 45° Offset Door Pulls



### Specifications:

#### MATERIAL:

Aluminum, Brass, Bronze, or Stainless Steel

#### FASTENER:

1/4"-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

#### OPTIONS:

- Back to back mounting in pairs — use BTB suffix and mounting type number (BF169BTB16)
- Concealed mounting single pulls — use C suffix and mounting type number (BF169C17)
- Advise if door thickness is other than 1 3/4"
- Heavy duty versions of most fastening types available — use suffix HD to fastening type number (BF169BTB16HD)
- Use Y prefix (YBF169) when ordering pulls with base plates, Y plate diameter is 1 1/4"; recommended for use on wood and glass doors

### Available Finishes:

- US28/628
- 313/710
- 315/711
- Powder Coat
- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630
- US32/629
- US32DMS
- US32D316
- US32316

MATERIAL SIZE:  
1" dia.

CTC:  
18"

OVERALL:  
19"

BASE:  
1"

PROJECTION:  
3 1/2"

CLEARANCE:  
2 1/2"

OFFSET:  
2 3/4"

WEIGHT:  
5.0 lbs.

ANSI A156.6: J402