

45° Offset Door Pulls No. BF160, BF161, BF162

Material: Aluminum, brass, bronze, stainless steel

Finishes: Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

Fastener: $\frac{1}{4} - 20 \times \frac{21}{4}$ " thru bolt & finish washer (standard $\frac{13}{4}$ " door)

- **Options:** Back to back mounting in pairs use BTB suffix and mounting type number (BF160BTB16)
 - Concealed mounting single pulls use C suffix and mounting type number (BF160C17)
 - \bullet Advise if door thickness is other than $1^3/4"$
 - See page B27 for mounting selection (standard duty 1/4 20).
 - \bullet Use Y prefix (YBF160) when ordering pulls with base plates, Y plate diameter is $1^1/_{16}$; recommended for use on wood and glass doors

No.	Material Size	СТС	Overall	Base	Projection	Clearance	Offset	Weight	ANSI A156.6
BF160	³ /4" dia.	8"	8 ³ /4"	³ /4"	31/4"	2 ¹ / ₂ "	3"	1.8 lbs.	J402
BF161	³ /4" dia.	10"	10 ³ /4"	³ /4"	31/4"	2 ¹ /2"	3"	2.0 lbs.	J402
BF162	³ /4" dia.	12"	12 ³ /4"	³ /4"	31/4"	2 ¹ /2"	3"	2.2 lbs.	J402



45° Offset Door Pulls No. BF166, BF167A, BF167, BF168, BF169

Material: Aluminum, brass, bronze, stainless steel

Finishes: Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

Fastener: ¹/₄-20x2¹/₄" thru bolt & finish washer (standard 1³/₄" door)

- **Options:** Back to back mounting in pairs use BTB suffix and mounting type number (BF166BTB16)
 - Concealed mounting single pulls use C suffix and mounting type number (BF166C17)
 - Advise if door thickness is other than 1³/4"
 - Heavy duty versions of most fastening types available use suffix HD to fastening type number (BF166BTB16HD)
 - See page B27 for mounting selection (standard duty 1/4 20)
 - Use Y prefix (YBF16) when ordering pulls with base plates, Y plate diameter is $1^{1}/_{4}$ "; recommended for use on wood and glass doors

No.	Material Size	СТС	Overall	Base	Projection	Clearance	Offset	Weight	ANSI A156.6
BF166	1" dia.	8"	9"	1"	3 ¹ / ₂ "	2 ¹ / ₂ "	3"	2.8 lbs.	J402
BF167A	1" dia.	9"	10"	1"	3 ¹ / ₂ "	2 ¹ / ₂ "	3"	3.0 lbs.	J402
BF167	1" dia.	10"	11"	1"	3 ¹ / ₂ "	2 ¹ /2"	3"	3.2 lbs.	J402
BF168	1" dia.	12"	13"	1"	3 ¹ /2"	2 ¹ /2"	3"	3.6 lbs.	J402
BF169	1" dia.	18"	19"	1"	3 ¹ /2"	2 ¹ /2"	3"	5.0 lbs.	J402

ASSA ABLOY

800-458-2424 | www.rockwoodmfg.com Check the web site for the up-to-date catalog

Copyright © 2012-2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited. The global leader in door opening solutions